








## KLICK TRACK SYSTEM REQUEST FORM

Track System / Mounting / Fixtures / Driver

PROJECT INFORMATION	
Project Name	
Company Name	
Sales Agent	
Track Quantity	
Date	REQ. Date

### Track System

1 - Select a Track shape.

<b>LINEAR TRACK</b> 	<b>L-SHAPE TRACK</b> 	<b>U-SHAPE TRACK</b> 	<b>RECTANGLE TRACK</b> 	<b>T-SHAPE TRACK</b> 	<b>X-SHAPE TRACK</b> 	<b>CUSTOM TRACK</b> 
---	---	---	---	--	---	--

2 - Enter numeric length(s) for tracks, using designated letter, for individual sides.

<b>A</b> FEET INCHES <input type="text"/>	<b>B</b> FEET INCHES <input type="text"/>	<b>C</b> FEET INCHES <input type="text"/>	<b>D</b> FEET INCHES <input type="text"/>	<b>** PROVIDE LENGTHS AND SHAPES FOR FACTORY APPROVAL**</b>
--	--	--	--	---

3 - Select the amount of track channels. 2 and 3 will be ganged together.

<input type="checkbox"/> <b>SINGLE TRACK</b> 1 Channel/Circuit	<input type="checkbox"/> <b>DOUBLE TRACK</b> 2 Channels/Circuits	<input type="checkbox"/> <b>TRIPLE TRACK (MAX)</b> 3 Channels/Circuits
---	---	---

4 - Select exterior panel color, inner track is anodized black only.

<input type="checkbox"/> <b>ANODIZED BLACK</b> Black track with black panels.	<input type="checkbox"/> <b>FLAT WHITE</b> Black track with white panels.	<input type="checkbox"/> <b>CUSTOM COLOR</b> Provide RAL number for factory approval
--	--	---

### Mounting Option

5 - Select a Track mounting option.

<input type="checkbox"/> <b>SURFACE</b> Drilled directly to mountable surface.	<input type="checkbox"/> <b>RECESSED</b> Recessed track, Mounting clips included.	<input type="checkbox"/> <b>TRIMLESS</b> Recessed track + white mud-in side panels.	<input type="checkbox"/> <b>SUSPENDED</b> Using air craft cables. (60" cable standard)	<input type="checkbox"/> <b>PRECISION PRO DRYWALL</b> Liteline custom drywall channel, with surface mount track inside.
---	--	--	---	--

6 - Enter the Power Feed length Required.

FEET	INCHES	<b>POWER FEED(S)</b> Length Req.
<input type="text"/>	<input type="text"/>	

7 - Enter the Suspension Cable length Required.

FEET	INCHES	<b>SUSPENSION CABLE(S)</b> Length Req.
<input type="text"/>	<input type="text"/>	

<input type="checkbox"/> 1/2" DRYWALL THICKNESS	<input type="checkbox"/> 5/8" DRYWALL THICKNESS
---	---

8 - Insulation Contact?

<input type="checkbox"/> YES	<input type="checkbox"/> NO
------------------------------	-----------------------------

9 - Select the Ceiling type the track is being mounted on.

<input type="checkbox"/> <b>HARD CEILING</b>	<input type="checkbox"/> <b>GRID T-BAR</b>	<input type="checkbox"/> <b>WOOD SLATS</b>	<input type="checkbox"/> <b>OTHER</b>
--	--	--	---------------------------------------

10 - Select the Required Canopy options, with colour.

<input type="checkbox"/> <b>BLACK</b>	<input type="checkbox"/> <b>WHITE</b>	<input type="checkbox"/> <b>CABLE CANOPY</b> Jbox Cover / Aircraft Canopies	<input type="checkbox"/> <b>BLACK</b>	<input type="checkbox"/> <b>WHITE</b>	<input type="checkbox"/> <b>DRIVER CANOPY</b> Driver Box
---------------------------------------	---------------------------------------	--	---------------------------------------	---------------------------------------	---

### Fixture Selection

11 - Select Fixture Colour.

<input type="checkbox"/> <b>BLACK FIXTURES</b>	<input type="checkbox"/> <b>WHITE FIXTURES</b>
--	--

13 - Select Fixture temperature.

<input type="checkbox"/> <b>3000K</b>	<input type="checkbox"/> <b>3500K</b>
---------------------------------------	---------------------------------------

12 - Select Fixtures type(s) by entering quantites required in each box.

<input type="checkbox"/> <b>ADJUSTABLE SPOT 10°</b> 10° / 10W / 429lm	<input type="checkbox"/> <b>MULTISOURCE LINE 5</b> 30° / 11W / 877lm	<input type="checkbox"/> <b>DOUBLE SPOT TWIN 30</b> 30° / 5W / 329lm	<input type="checkbox"/> <b>PENDANT CYLINDER</b> 20° / 10W / 389lm
<input type="checkbox"/> <b>ADJUSTABLE SPOT 20°</b> 20° / 10W / 429lm	<input type="checkbox"/> <b>MULTISOURCE LINE 10</b> 30° / 22w / 1773lm	<input type="checkbox"/> <b>DOUBLE SPOT TWIN 60</b> 62° / 5W / 180lm	<input type="checkbox"/> <b>KL-BAR</b> Please refer to KLICK BAR Series ordering guide.(12'-96")
<input type="checkbox"/> <b>ADJUSTABLE LINE 5</b> 30° / 11W / 877lm	<input type="checkbox"/> <b>MULTISOURCE LINE 15</b> 30° / 33w / 2669lm	<input type="checkbox"/> <b>WALL WASH</b> 90° / 11W / 384lm	<input type="button" value="CLICK HERE FOR ORDERING GUIDE"/>

### Driver Type

14 - Select the type of Dimming req.

<input type="checkbox"/> <b>TRIAC / ELV DIMMING</b> (80W)	<input type="checkbox"/> <b>0 - 10 VOLT DIMMING</b> (80W)
--	--

16 - Select a Track Power entry point.

<input type="checkbox"/> <b>END CAP</b> Beginning of track	<input type="checkbox"/> <b>CENTER</b> Center fed
<input type="checkbox"/> <b>MULTIPLES</b> Split by individual side, on shape	<input type="checkbox"/> <b>MULTIPLES</b> Split evenly by length across shape

15 - Select the amount of Drivers necessary.

<input type="checkbox"/> <b>1 DRIVER (80W)</b> Suggested for small tracks, and or small shapes - (< 20FT)	<input type="checkbox"/> <b>2 DRIVERS (160W)</b> Suggested for mid size tracks and L-shape systems - (20-40FT)
<input type="checkbox"/> <b>3 DRIVERS (240W)</b> Suggested for larger tracks and L-T-U shaped systems - (40-60FT)	<input type="checkbox"/> <b>4 DRIVERS (320W)</b> Suggested for very lengthy tracks and rectangles - (60-80FT)

17 - Select Distance between the Track and Driver.

<input type="checkbox"/> 0'-5'	<input type="checkbox"/> 5'-10'	<input type="checkbox"/> 10'-15'	<input type="checkbox"/> 15'-20'	<input type="checkbox"/> 25+
<b>RECOMMENDED DRIVER TO TRACK DISTANCE</b>				<b>MAX WATTAGE WILL DROP AFTER 20FT</b>
<b>** SPECIAL PRECAUTIONS MUST BE TAKEN TO POWER FROM 25 FEET PLUS. THE MAX WATTAGE WILL SIGNIFICANTLY DROP. PLEASE INQUIRE WITH LOCAL LITELINE SALES AGENT WHEN ORDERING AT THIS DISTANCE **</b>				

- Consider necessary Lumens needed in desired space  
- Consider available fixture space to available track length

COSTUMER NOTES :